

VNR-E216

16CH 1U Network Video Recorder



5.0

MP Resolution



1080P

80/16/32 CH



Up to 4TB



Motion Detection



200

Mbps MAX



HDMI/VGA



3D Positioning




Real Time Playback

- › Up to 16 channel with 1080P realtime live view
- › H.264/MJPEG dual codec decoding
- › Max 200Mbps incoming bandwidth
- › Up to 5Mp resolution preview&playback
- › HDMI/VGA simultaneous video output
- › 16 channel synchronous realtime playback, GRID interface
- › Support Multi-brand network cameras
- › ONVIF Version 2.3 conformance
- › 3D intelligent positioning with Visilex PTZ camera
- › Support 2 SATA HDDs up to 8TB, 2 USB(1 USB3.0)
- › Support IPC UPnP
- › Multiple network monitoring: Web viewer, CMS(XStation) & VisiMob

Technical Specifications

System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Video & Audio	
IP Camera Input	16 Channel
Two-way Talk	1channel Input, 1channel Output, RCA
Display	
Interface	1 HDMI,1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Compression	H.264 / MJPEG
Resolution	5Mp (2560×1920) /3Mp (2048×1536) /1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)&etc.
Record Rate	200Mbps
Bit Rate	48~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input	4 channel
Relay Output	2 channel
Playback & Backup	
Sync Playback	1/4/8/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner
Network	
Ethernet	1 RJ-45 port (10/100/1000Mbps)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Visilex IP camera, DVR, NVS and etc.)

Max. User Access	128 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	2 SATA ports, up to 8TB, Raid (Redundancy)
Auxiliary Interface	
USB	2 ports (1 Rear USB3.0,1 Front USB2.0)
RS232	1 port, For PC communication&Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	DC12V/4A
Power Consumption	20W(without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH / 86~106kpa
Dimension(W×D×H)	1U, 375mm×285mm×50mm
Weight	2.0KG(without HDD)



www.visilex.com



Visilex Technologies

Baererstr- 22A, Hamburg, 21073, Germany

☎ +49 176 72643084 ✉ sales@visilex.com

Design and specifications are subject to change without notice
© 2014 Visilex Technologies