

# VISILEX



## VFN-2360P / 2360N

2 Megapixel Full HD Network Fish - Eye Camera



- › 1/2.8" 2Megapixel progressive scan Exmor CMOS
- › H.264 & MJPEG dual-stream encoding
- › Max25/30fps@1080P&25/30fps@SXGA&25/30fps @720P(1280×720)
- › DC12V, PoE
- › Day/Night, 2DNR, AWB, AGC, BLC
- › 1.25mm Fish-Eye lens
- › Multiple network monitoring: Web viewer, CMS(XStation) & VisiMob

## Technical Specifications

	VFN-2360P	VFN-2360N
<b>Camera</b>		
Image Sensor	1/3" 2Megapixel Exmor CMOS	
Effective Pixels	1920(H)x1080(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual 1/3~1/10000	Auto/Manual 1/4~1/10000
Min. Illumination	Color: 0. 1LUX/F1.4	
S/N Ratio	>50dB	

<b>Camera Features</b>	
Day/Night	Auto(Electronic) / Color / B/W
Backlight Compensation	BLC
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas

<b>Lens</b>	
Focal Length	1.25mm
Max Aperture	F1.8
Angle of View	H: 180°±5°
Mount Type	Board-in Type

<b>Video</b>		
Compression	H.264 / MJPEG	
Resolution	11080P(1920×1080)/ SXGA (1280×1024)720P(1280× 720)/ D1(704×576) / CIF(352×288)/	1080P(1920×1080)/ SXGA(1280× 1024)720P(1280×72 0)/ D1(704×576) / CIF(352×288)/
Frame Rate	Main Stream	1080P(1~30fps)/SXGA(1~30fps)/720P(1 ~ 25/30fps)
	SubStream	D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 56K ~ 8192Kbps	

<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Profile S
Max. User Access	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone

General	
Power Supply	DC12V, PoE(802.3af)
Memory Slot	Micro SD
Power Consumption	<2.5W
Working Environment	-10°C~+60°C, 10%~90%
Dimensions	Φ110×54mm
Weight	0.25kg

